

**N 90, Gas cooktop, 90 cm, Ceramic,  
Black  
T29TA79N0A**



The gas cooktop with an extremely heat-resistant ceramic glass surface and incrementally adjustable FlameSelect.

✓ FlameSelect: 9 levels of precisely controlled flame height. Simply note which number you use and the result will be the same everytime.

#### Features

##### Technical Data

Product name/family : gas cooktop w integrated controls  
Built-in / Free-standing : Built-in  
Energy input : Gas  
Total number of positions that can be used at the same time : 5  
Type of control setting devices : Sword knobs  
Required niche size for installation (HxWxD) : 45 x 850-852 x 490-502 mm  
Width of the appliance : 918 mm  
Dimensions (HxWxD) : 45x918x546 mm  
Dimensions of the packed product (HxWxD) : 165x1110x659 mm  
Net weight : 20.6 kg  
Gross weight : 23.0 kg  
Residual heat indicator : separate  
Location of control panel : Front  
Basic surface material : Ceramic  
Color of surface : Black, Stainless steel  
Color of frame : Black, Stainless steel  
Length electrical supply cord : 100 cm  
EAN code : 4242004218173  
Gas connection rating : 13700 W  
Fuse protection : 3 A  
Voltage : 220-240 V  
Frequency : 50; 60 Hz



4 242004 218173

# N 90, Gas cooktop, 90 cm, Ceramic, Black T29TA79N0A

## Features

### Design

- Ceramic glass
- brushed steel trim frame
- Design burner - special flat design

### Comfort & Convenience

- FlameSelect (9 steps)
- Digital display
- Sword control knobs
- One-hand ignition
- Enamelled cast iron pan supports on non-scratch rubber feet

### Size & Power

- 5 Gas burners
- Dual flame wok burner
- 1 High-speed, 2 Standard, 1 Economy, 1 Dual Wok burner
- Left: Wok burner up to 22 MJ/h (depending on gas type)
- Center rear: Economy burner up to 4.8 MJ/h (depending on gas type)
- Center front: Standard burner up to 8.1 MJ/h (depending on gas type)
- Right rear: High-speed burner up to 11.6 MJ/h (depending on gas type)
- Right front: Standard burner 8.1 MJ/h (depending on gas type)
- Additional tools for LPG conversion required: removal lever (483196) and spanner (269605).

### Safety and Environment

- Flame failure device fitted to each individual burner
- Residual heat indicator for each burner
- Preset to natural gas (20mbar)

### Dimensions (WxD)

- 90 cm width
- Installation measurements: 850 mm x 490 mm
- Power cord length: 100 cm

### Supplied Accessories

- Liquid gas nozzles (28-30/37mbar) included
- 1 x Wok attachment ring, cross support for espresso included.

**T29TA79N0A**

## Dimensioned drawings

