Sp	ecifications		
Model No.			X5V09S
Ноо	d Mounting	Wall Mounted Canopy	
S	Hood Width		900mm
Dimensions	Hood Depth		500mm
	Hood Height (Fasci	ia)	120mm
Cool	king Surface Covera	nge (cm)	75-100cm
	Install Height	600mm	
Recommended Install Height			700-750mm
Indu	iction Suitable		•
Char Grill Suitable			-
□ AISI304 1.2mm Food Grade			•
Finish	AISI316 1.2mm Marine Grade		-
Filtration	Type: S-Flow Baffle	9	•
Ē	Filter Quantity		3
	MasterMind		•
Electronics	Controls		4-Button Backlit LED MasterMind Electronic Cont
	Wireless Remote		0
	Speed Settings		3 Speed + Boost Mode
ш	Timer Function		Programmable Timer 10min Increments
	Auto Fan Shut Off		Auto Off After 2-Hours Of Inactivity
	Type: LED - Warm White		•
g	Type: LED - Cool White		0
Jhtim	Lamp Quantity	5	
Ĭ	Front Panel	•	
	Rear Panel		•
	Outlet Position - Top		•
	Outlet Position - Rear		0
Exhaust	Outlet Quantity		1
X	Ducting (Remote Motor)		Zilikon Duct - Dia. 200mm 5M Length Supplied
	Ducting (Onboard Motor) Not Supplied - Duct Kits Available		Power Motor - Dia. 150mr Ultra Motor - Dia. 200mm
SELE	ECT YOUR HOOD & TOR COMBINATION		X5V09S5 / X5V09S6
(VIOT)	Power 1020 - Top	1020m³/hr	.OP/T
pard	Power 1020 - Rear	1020m³/hr	.OP/B
On Board	Ultra 1680 - Top	1680m³/hr	.0U/T
	Ultra 1680 - Rear	1680m³/hr	.OU/B
Je	Lite 800	800m³/hr	.IL

	CT YOUR HOOD & OR COMBINATION	X5V09S5 / X5V09S6	
On Board	Power 1020 - Top	1020m³/hr	.OP/T
	Power 1020 - Rear	1020m³/hr	.OP/B
	Ultra 1680 - Top	1680m³/hr	.0U/T
	Ultra 1680 - Rear	1680m³/hr	.0U/B
Inline	Lite 800	800m³/hr	.IL
	Pro 1140	1140m³/hr	.IP
External	Lite 800	800m³/hr	.EL
	Pro 1140	1140m³/hr	.EP
	Pro Plus 2010	2010m³/hr	.EPP
Standard Inclusion			- Not Available

Standard Inclusion









5 YEAR WARRANTY
OMPRESENCE WARRS & LABOUR







Your Hood. Your Colour. Your Way. Select your hood finish.

















Dimensioned Drawing

